



## ■ 技术参数 SPECIFICATIONS

- 适用线规 (Applicable wires) : AWG20#~14#
- 温度范围 (Temperature range) : -25℃~85℃
- 额定电压 (Voltage rating) : 300V.Ac/Dc
- 额定电流 (Current rating) : 15A
- 接触电阻 (Contact resistance) :  $\leq 0.01\Omega$
- 绝缘电阻 (Insulation resistance) :  $\geq 1000M\Omega$
- 耐压 (Withstand voltage) : 2000V.Ac/1min
- 材料 (Material) :
  - 壳体 (Housing) : 尼龙 (PA66) UL94V-2(0)
  - 端子 (Terminal) : 黄铜 (Brass Tin/plated)
- 端子锁紧力 (Terminal Locking Force) : 10kg/min
- 保持力 (Retentive Force) : 6.0kg/min

### .187/.250" 端子 TERMINAL

型号 Type	适用线规 Applicable wires	尺寸 Dimensions (mm)				数量 Quantity		
		mm <sup>2</sup>	AWG#	W	L		E	材料厚度 Thickness
HX4.8S-01T	730567-3	0.22~0.5	24~20	5.6	19.3	5.1	0.3	10000PCS/卷
HX4.8S-21T	730568-3	0.55~1.28	20~16					
HX4.8S-41T	730569-3	0.76~2.09	18~14					
HX6.3S-21T	730571-3	0.76~2.09	18~14	7.6	23.2	6.6	0.4	5000PCS/卷
HX6.3S-41T	730572-3	1.75~5.4 ( $\phi 0.8$ SOLID)	12~10					

型号 Type	尺寸 Dimensions (mm)				
	A	B	C	D	F
.187"	7.0	3.6	4.8	$\phi 1.5$	0.5
.250"	8.3	3.8	6.35	$\phi 2.0$	0.8

### 6.3(.250") 壳体 HOUSING

型号 Type	尺寸 Dimensions (mm)			适配端子 Suitable Terminal
	L	T	W	
HX6.3S-1P (630591.250) (35196-0110)	28.0	7.5	9.0	HX6.3S-21T HX6.3S-41T

型号 Type	尺寸 Dimensions (mm)			适配端子 Suitable Terminal
	L	T	W	
HX4.8K-2P (631980.187+.250)	28.2	13.6	9.0	HX4.8S-01T HX4.8S-21T HX4.8S-41T HX6.3S-21T HX6.3S-41T